



**DDZR.MH26624**  
**Liners**

---

**Liners**

See General Information for Liners

**NORTH AMERICAN SUPAFLU SYSTEMS INC**

MH26624

UNIT 203

15 HOLLY ST

PO BOX 2350

SCARBOROUGH, ME 04070 USA

Supaflu Type "HT", Cementitious Chimney Lining System. In sizes 4 thru 16 in. I.D. For use as an alternate lining system for fire-clay flue linings in masonry chimneys intended for use with gas, liquid and solid fuel-fired residential and building heating appliances intended for use with Type B vents. Clearance between combustible construction and outer chimney surfaces is zero (0) in. Minimum chimney liner thickness from I.D. of chimney liner to masonry chimney is 5/8 in. For maximum chimney height of 80 ft.

Last Updated on 2000-04-27

---

Copyright © 2010 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2010 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

