



AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the Product Covered described below herein when made in accordance with the authorized Listing Report, including Manufacturing/Machining Specifications, and under conditions set forth in the Certification Agreement and Listing Report, including Manufacturing/Machining Specifications. This authorization also applies to the Multiple Listee model(s) identified on the correlation page of the Listing Report.

Client Number: 15165 **Report Number:** 3096271, J97018322.1, 652-0353.01, 694-0198.0, 694-0198.1

Evaluation Center: Intertek (Middleton)

Applicant/Basic Listee: North American Supaflu Systems, Inc.
15 Holly Street U203
Scarborough, ME 04074

Contact: **Name:** Fred Howes
Phone: 207-883-1155 **Fax:** 207-885-0561

Product Covered: North American Supaflu Systems Chimney Liner

Testing Standards: UL 1777 (2004) ULC S635 (2000) ULC S640 (1991)

This document is the property of Intertek Testing Services and is not transferable. Only the Applicant may reproduce this document. The Certification Mark(s) may be applied only at the above noted location of the Party Authorized to Apply the Mark(s).



This document supersedes all previous Authorizations to Mark for the noted Report Number.

Authorized By: 
Bob Davison, Certification Manager, Toronto Center

Intertek Testing Services Ltd.
3210 American Drive, Mississauga, ON L4V 1B3 Canada
Phone 905-678-7820 Fax 905-678-7131

Listing Section:

Description:

Product Covered:

Supaflu Chimney Liner

Product Description:

Supaflu liners are installed only by qualified technicians who have been trained by the manufacturer. The technicians are provided with a training manual, which gives thorough instructions for proper installation of the Supaflu liner. The Supaflu mix is a cementitious material with light weight aggregates manufactured in dry powder form and sold to factory trained dealers in 60 pound bags. The powder is mixed at the job site with water, approximately 5 1/2 U.S. gallons per 60 pound bag. The wet mix is pumped around an inflatable tubular from within the chimney and allowed to cure. The formulation is proprietary and the exact formula is in the custody of the manufacturer.

**Party Authorized To Apply
Mark:**

Intertek ETL SEMKO
8431 Murphy Drive
Middleton WI 53562
Wendy Orth
866-262-2753
wendy.orth@intertek.com